

:::JYD MATERIALES ELECTRICOS:::

JYD Materiales Eléctricos

GPT, SGT(BA), HTT(I)




ESPECIFICACIONES CONDUCTORES TIPO GPT


CALIBRE CONDUCTOR	
----------------------	--

SECCION


NOMINAL



**NUMERO
HILOS**



DIÁMETRO
HILO




ESPEJOR

AI SLAMI ENTO



**DIÁMETRO
NOMINAL**



PESO

NOMINAL

20	0,52		7	0,320	0,58	2,2	10	
18	0,82	16	0,254	0,58	2,5	12		
16	1,31	19	0,287	0,58	2,7	16		
14	2,08	19	0,361	0,58	3,1	25		
12	3,31	19	0,455	0,66	3,7	38		
10	5,26	19	0,574	0,79	4,5	57		
8	8,37	19	0,724	0,94	6,0	90		
TIPO SGT(BA)-CABLES PARA BATERIA								

mm
AWG mm²

6	13,30	49	0,588	1,35	8,0	165
4	21,15	49	0,741	1,45	9,7	250
2	33,63	133	0,574	1,66	11,9	394
1	42,41	133	0,643	1,66	13,0	485
1/0	53,48	133	0,724	1,66	14,2	601
2/0	67,43	133	0,803	1,66	15,3	740

TIPO HTT(I)-CABLE PARA BUJIA - TENSION DE SERVICIO 15Kv

CALIBRE AWG	SECCION NOMINAL mm ²	NUMERO HILOS	DIÁMETRO HILO mm	ESPEORES		DIÁMETRO mm	PESO Kg/Km
				AISLAMIENTO mm	CUBIERTA mm		
17	1,14	19	0,254	1,42	1,42	7,0	59

Â

[Información](#)