

**:::JYD MATERIALES ELECTRICOS:::***JYD Materiales Eléctricos***Control Tipo CCT-B****ESPECIFICACIONES CABLES DE CONTROL CCT - B**

NÂ° COND.	DIAMETRO	ESPEORES		DIAMETRO	PESO	C.CORRIENTE
X CALIBRE	CONDUCTOR	AISLAMIENTO	CUBIERTA	EXTERIOR	Â	(*)
AWG	mm	mm	mm	mm	Kg/Km	A
4 x 16	1,29	0,76	1,14	9	120	12
4 x 14	1,63	1,14	1,14	12	191	16
4 x 12	2,05	1,14	1,14	13	249	22
7 x 16	1,29	0,76	1,14	11	185	10
7 x 14	1,63	1,14	1,52	15	329	14
7 x 12	2,05	1,14	1,52	16	430	19
12 x 16	1,29	0,76	1,52	15	324	9

12 x 14	1,63	1,14	1,52	20	524	12
12 x 12	2,05	1,14	2,03	22	751	16
19 x 16	1,29	0,76	1,52	17	470	8
19 x 14	1,63	1,14	2,03	24	835	10
19 x 12	2,05	1,14	2,03	26	1104	14

(\*) -TEMPERATURA EN EL CONDUCTOR 80Â°C

Â -TEMPERATURA AMBIENTE 40Â°C

Â -CONDUCTORES SIMULTANEAMENTE CARGADOS

[Informaci3n](#)